


























CASCADE
LUXURY VINYL



www.cascadeluxuryvinyl.com

Creative
Options



				
CR0502 Driftwood 7"	CR0504 Thunder Cloud 7"	CR0514 Barn Barrel 7"	CR0515 Saltwood 7"	CR0516 Skyfall Grey 7"
				
CR0521 Almond Toffee 7"	CR05966 Cobblestone 9"	CR0522 Foghorn 7"	CR0523 Warm Cinnamon 7"	CR0527 Soft Pearl 7"
				
CR05936 Colonial 9"	CR0567 Brushed Nickel 7"	CR05965 Chamomille 9"	CR0533 Monarch Oak 7"	CR05934 Courtyard Oak 9"
				
CR05935 Millennium Oak 9"	CR05987 Bianco Maple 9"	CR05T37 Boulder Grey 12.36"	CR05T39 Mercury 12.36"	CR0593 - Boutique Beige
				
CR0594 - Snow Dust	CR05959 - Cotton Wood 9"	CR05975 - Holiday Natural 9"		



CREATIVE OPTIONS SPECIFICATIONS

Construction	LVT
Thickness	5mm
Wear Layer	0.5mm 20 mil
Size	7" x 48", 9" x 48" & 12.36" x 24.6"
Finish	Polyurethane w/ anti bacterial nano silver, ultra matte
Edge Detail	Square edge
Sf Per Carton	7" 23.33, 9" 23.94, 12.36" 21.10
Sf Per Pallet	7" x 48" = 1,166.50 9" x 48" = 1,244.88 12.36" x 24.6" = 1,181.6
Installation	Loose Lay (glue down optional)
Backing	Anti Skid / Acoustic
Classification	Best
Residential Warranty	Lifetime Limited Residential
Commercial Warranty	12 Year Limited Heavy Commercial
Recommended Adhesive	Cascade XT360
Approved Adhesives	Wolf Grip Premium Armstrong - 995

PERFORMANCE TESTING

Reaction To Fire	EN ISO 11925-2 Pass EN ISO 9239-1 Pass
Chemical Resistance	ASTM F925 Pass
Light Resistance	ASTM F1515 < 8
Wear Resistance	ASTM F510 Wear group P EN 434 ≤ 0.25%
Static Electrical Propensity	0.5kV
Residual Indentation	EN ISO 24343-1 Avg 0.02mm
Anti-Slip Property	DIN 51130 R10
Voc Emission	ISO 16000 A+
Phalates	EN 14372 N.D. CPSC-CH-C 1101 Pass
Castor Chair	ISO 4918 Pass

Creative
Options

