




CASCADE
LUXURY VINYL


IMPACT
LUXURY VINYL TILE




IMP02 Electric Grey




IMP04 Park Ave Slate




IMP09 Rodeo Mist




IMP10 Sunset Khaki




IMP12 Wall St Steel




IMP66 Cathedral Brown



IMP17 Camben St Tan



IMP56 Roasted Truffe



IMP26 Bedrock




IMP27 Arctic Express




IMP20 Canal St Fawn




IMP22 Victoria Grey




IMP28 Frosted Grey




IMP50 Duke St Wash




IMP55 Iron Wood




IMP85 Sandalwood




IMP67 Wolf Grey




IMP69 Lighthouse Oak




IMP84 Apple Wood




IMPT74 Urban Slab




IMP80 Cabana Natural



IMP83 Light Latte



IMP88 - Orchard Grey



IMP89 - Hollywood Blonde



IMP90 - Beale St Beige



IMP91 - Central Park Snow



IMP92 - Robson Russet



IMPACT SPECIFICATIONS

Constructions	PVC
Thickness	2mm
Wear Layer	0.3mm 12 mil
Size	7" x 48" / 12.36" x 24.6"
Finish	Polyurethane w/ anti bacterial nano silver, satin gloss
Edge Detail	Square edge
Sf Per Carton	12.36" x 24.6" = 52.81" 7" x 48" = 51.33
Sf Per Pallet	12.36" x 24.6" = 24.6" = 2,746.12 7" x 48" = 3,079.80
Installation	Glue Down
Classification	Good
Residential Warranty	25 Year Limited Residential
Commercial Warranty	10 Year Limited Medium Commercial
Recommended Adhesive	Cascade XT360
Approved Adhesives	Wolf Grip Premium, Armstrong S - 995.
Emissions	FloorScore Certified

PERFORMANCE TESTING

Fire Rating	ASTM E84 75 or less
Mekel Burner Test	Pass
Heat Stability	KSM 3802 0.3mm/ 0.01"80C+2C, 6hr/1hr
Abrasion Resistance	ASTM D3884 0.1% Loss
Slip Resistance ADA	Exceeds ADA Requirements
Dry Static Coefficient Of Friction	ASTM C1028 0.72
Wet Static Coefficient Of Friction	ASTM C1028 0.67
Residual Indentation	EN 433 ≤ 0.10mm
Color Fastness	ISO 105-B02 ≥ 6
Dimensional Stability	EN 434 ≤ 0.10mm
Flexibility	EN 435 No crack was found
Electrical Behavior	EN 1081 Pass
CAN/UCL 102.2	FRS: 15 SDC:190

IMPACT
LUXURY VINYL TILE

