

Product quality		
Formats		840 x 140 x 9,0 mm
Packaging	Pack:	11 elements / 1,294 m ² / 10,1 kg
	Pallet:	56 packs / 72,44 m ² / 580,6 kg

Tolerances (Requirement EN 16511:2023)		
Squareness of the elements ($\leq 0.50\text{mm}$)		$\leq 0,15\text{ mm}$
Determination of Linearity ($\leq 0.30\text{ mm/m}$)		$\leq 0,20\text{ mm/m}$
Flatness concave / convex	lengthwise ($\leq 0.50 / \leq 1.0\%$)	$\leq 0,35 / \leq 1,0\%$
	wide ($\leq 0.10 / \leq 0.15\%$)	$\leq 0,10 / \leq 0,15\%$
Height difference	(average $\leq 0.15\text{ mm}$)	(average $\leq 0.10\text{ mm}$)
	(max. $\leq 0.20\text{ mm}$)	(max. $\leq 0.15\text{ mm}$)
Opening between installed elements	(average $\leq 0.15\text{ mm}$)	(average $\leq 0.05\text{ mm}$)
	(max. $\leq 0.20\text{ mm}$)	(max. $\leq 0.10\text{ mm}$)

Guarantee (according Parador guarantee conditions)		Notes
Domestic area	Commercial area	- suitable for all-over adhesion (up to max. 20sqm)
Lifetime	10 Years	- cleaning and maintenance see instructions
		- technical changes reserved
      		

Classification (acc. EN 16511:2023)		
		
Utility class 23 = domestic areas with intensive use		Utility class 33 = commercial areas with intensive use
The design floor meets all requirements of the designated use class.		
Requirements / properties	Test method	Rating
 Reaction to fire	EN 13501-1	C _s s1
 Slip resistance	EN 13893 EN 14041	$\mu \geq 0,30$ DS
 Staining resistance	EN 438-2	Category 1 + 2: level 5, no visible change Category 3: level 4, slight change
 Light fastness	EN ISO 105 – B02	Blue wool scale: Stage ≥ 6
 Resistance to roller castor chairs	EN ISO 4918	Type W, no visible changes
 Thermal resistance Suitable for installation over underfloor heating when using an appropriate moisture barrier.	EN 12667	0,084 m ² *K/W
 Moving a furniture leg	EN ISO 16581	No visible damage (foot type 0)
 Residual indentation	EN ISO 24343-1	$\leq 0,05\text{ mm}$
 Formaldehyde emission (E1 = 0.1 ppm)	ISO 16000	$\leq 0,05\text{ ppm}$
 Acoustical - Impact noise reduction	EN ISO 10140-3	18 dB (auf PE-Folie)
 Locking strength	ISO 24334	lengthwise $\geq 1\text{ kN/m}$ transversely * kN/m (* not reportable due to construction)
 Abrasion	ISO 24338, Annex B	> 7.000 rev.
 Impact resistance	EN 13329 Annex F	$\geq 1.800\text{ mm}$
 Dimensional stability after exposure to temperature	EN ISO 23999	$\leq 0,15\%$
Water resistance	ISO 4760	Requirements met (1h instead of 24h)
Micro scratch resistance	EN 16094	Method A MSR-A2 For mat surfaces (gloss ≤ 7): ≤ 1.5 unit change at 60°
Slip resistance	EN 16165, Annex B on an inclined plane EN 16165, Annex C pendulum test	Authentic texture: R10 PTV (dry (slider 96)) ≥ 36 Low slip potential according to UK Slip resistance group
Disposal	EAK-Code-number	17 09 04

Changed:	QMB Parador	File:	PA_TDS_Designboden_Modular-ONE_Fischgrät_EN_20260601
Date:	01/11/2023	Latest update at:	https://parador.de/en/services/downloads/design-flooring
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01/06/2026