

| Product quality                                                                                                                                                                                                                                                                                                                                                                                                           |                 |                                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------------------------------------------|
| Format                                                                                                                                                                                                                                                                                                                                                                                                                    |                 | 488 x 118 x 2.5 mm                          |
| Packaging                                                                                                                                                                                                                                                                                                                                                                                                                 | Pack:           | 30 elements / 1.728 m² / 7.59 kg            |
|                                                                                                                                                                                                                                                                                                                                                                                                                           | Palette:        | 132 packs / 228.096 m² / 1,037.88 kg        |
| Tolerances (requirement EN ISO 10582)                                                                                                                                                                                                                                                                                                                                                                                     |                 |                                             |
| Weight per unit area                                                                                                                                                                                                                                                                                                                                                                                                      |                 | 4.300 g/m2 ± 5%                             |
| Squareness of the elements (≤ 0.25 mm)                                                                                                                                                                                                                                                                                                                                                                                    |                 | ≤ 0,10 mm/m                                 |
| Determination of linearity (≤ 0.35 mm/m)                                                                                                                                                                                                                                                                                                                                                                                  |                 | ≤ 0,20 mm/m                                 |
| Dimensional stability after exposure to heat (≤ 0,15 %)                                                                                                                                                                                                                                                                                                                                                                   |                 | ≤ 0,15 %                                    |
| Curling after exposure to heat (≤ 1mm)                                                                                                                                                                                                                                                                                                                                                                                    |                 | ≤ 1mm                                       |
|                                                                                                                                                                                                                                                                                                                                                                                                                           |                 |                                             |
| Guarantee (According Parador guarantee conditions)                                                                                                                                                                                                                                                                                                                                                                        |                 | Notes                                       |
| Domestic area                                                                                                                                                                                                                                                                                                                                                                                                             | Commercial area | - only suitable for all-over adhesion       |
| Lifetime                                                                                                                                                                                                                                                                                                                                                                                                                  | 10 years        | - cleaning and maintenance see instructions |
|                                                                                                                                                                                                                                                                                                                                                                                                                           |                 | - technical changes reserved                |
|                                                                                                                                                                                                                                                                                                                                                                                                                           |                 |                                             |
| <div><div><p>EN 14041:2004/AC:2006</p></div><div></div><div></div><div></div></div> |                 |                                             |

| Classification                                                                      |                                                                                |                                                                                    |                                                                                                           |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
|    |                                                                                |  |                                                                                                           |
| Utility class 23 = domestic areas with intensive use                                |                                                                                | Utility class 33 = commercial areas with intensive use                             |                                                                                                           |
| The design floor meets all requirements of the designated utility class.            |                                                                                |                                                                                    |                                                                                                           |
| Requirements / properties                                                           |                                                                                | Test method                                                                        | Rating                                                                                                    |
|    | Wear layer                                                                     | EN ISO 24340                                                                       | 0,55 mm                                                                                                   |
|                                                                                     | Surface Coating                                                                |                                                                                    | PUR                                                                                                       |
|    | Reaction to fire                                                               | EN 13501-1                                                                         | B <sub>f</sub> s1                                                                                         |
|   | Slip resistance                                                                | EN 13893<br>EN 14041                                                               | μ ≥ 0,30<br>DS                                                                                            |
|  | Staining resistance                                                            | ISO 26987                                                                          | Index 0, Not affected                                                                                     |
|  | Light fastness                                                                 | EN ISO 105 – B02                                                                   | Blue wool scale: Stage ≥ 6                                                                                |
|  | Resistance to roller castor chairs                                             | ISO 4918                                                                           | Type W, no visible changes                                                                                |
|  | <b>Thermal resistance</b><br>Suitable for installation over underfloor heating | EN 12664                                                                           | 0,012 m²*K/W                                                                                              |
|  | Moving a furniture leg                                                         | EN 424                                                                             | No visible changes                                                                                        |
|  | Indentation-residual                                                           | EN ISO 24343-1                                                                     | ≤ 0,10 mm                                                                                                 |
|                                                                                     | Water resistance                                                               | EN 317                                                                             | waterproof                                                                                                |
|                                                                                     | Antimicrobial activity                                                         | ISO 22196                                                                          | Antibacterial                                                                                             |
|                                                                                     | Slip resistance                                                                | EN 16165, Annex B<br>on an inclined plane                                          | Matt finished texture: R10                                                                                |
|                                                                                     |                                                                                | EN 16165, Annex C<br>pendulum test                                                 | PTV (dry / wet - slider 96) ≥ 40<br>PTV ≥ 36 = Low slip potential<br>according to UK Slip potential group |
|                                                                                     | Disposal                                                                       | EAK-Code-number                                                                    | 20 01 39                                                                                                  |

|                                                                                                                                                      |             |                   |                                                                                                                                |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Changed:                                                                                                                                             | QMB Parador | File:             | PA_TDS_Designboden_Vinyl_Dryback-TT10_EN_20260601                                                                              |
| Date:                                                                                                                                                | 01/01/2025  | Latest update at: | <a href="http://www.parador.de/en/services/downloads/design-flooring">www.parador.de/en/services/downloads/design-flooring</a> |
| Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from: |             |                   | 01/06/2026                                                                                                                     |