

Product quality		
Format		770 x 154 x 2,5 mm
Packaging	Pack:	20 elements / 2.372 m² / 10,417 kg
	Palette:	90 packs / 200.64 m² / 937.553 kg
Tolerances (requirement EN ISO 10582)		
Weight per unit area		4.300 g/m2 ± 5%
Squareness of the elements (≤ 0.25 mm)		≤ 0,10 mm/m
Determination of linearity (≤ 0.35 mm/m)		≤ 0,20 mm/m
Dimensional stability after exposure to heat (≤ 0,15 %)		≤ 0,15 %
Curling after exposure to heat (≤ 1mm)		≤ 1mm
Guarantee (According Parador guarantee conditions)		Notes
Domestic area	Commercial area	- only suitable for all-over adhesion - cleaning and maintenance see instructions - technical changes reserved
Lifetime	10 years	
 EN 14041:2004/AC:2006   		

Classification			
			
Utility class 23 = domestic areas with intensive use		Utility class 33 = commercial areas with intensive use	
The design floor meets all requirements of the designated utility class.			
Requirements / properties		Test method	Rating
	Wear layer	EN ISO 24340	0,55 mm
	Surface Coating		PUR
	Reaction to fire	EN 13501-1	B _n s1
	Slip resistance	EN 13893 EN 14041	μ ≥ 0,30 DS
	Staining resistance	ISO 26987	Index 0, Not affected
	Light fastness	EN ISO 105 – B02	Blue wool scale: Stage ≥ 6
	Resistance to roller castor chairs	ISO 4918	Type W, no visible changes
	Thermal resistance Suitable for installation over underfloor heating	EN 12664	0,012 m²·K/W
	Moving a furniture leg	EN 424	No visible changes
	Indentation-residual	EN ISO 24343-1	≤ 0,10 mm
	Water resistance	EN 317	waterproof
	Antimicrobial activity	ISO 22196	Antibacterial
	Slip resistance on an inclined plane	EN 16165, Annex B	Matt finished texture: R10
	Disposal	EAK-Code-number	20 01 39

Changed:	QMB Parador	File:	PA_TDS_Designboden_Vinyl_Dryback_Trendtime-3_EN_20260601
Date:	01/01/2018	Latest update at:	www.parador.de/en/services/downloads/design-flooring
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01/06/2026