

**1. PROPRIETARY PRODUCT/MANUFACTURER**

- 1.1. **Proprietary Product:** Luxury vinyl floor covering with Tarkett's Techtonic polyurethane comes in tile and plank form. Suitable for commercial working environments and offices:
- Education – Classrooms, corridors, multipurpose rooms, laboratories, cafeterias, lavatories
  - Offices – Break rooms, offices, corridors, cafeterias, lavatories
  - Retail – Sales areas, offices
  - Hospitality – Corridors, vending areas, lobbies
  - rooms, offices
  - Healthcare – Patient rooms, exam rooms, lobbies, corridors, emergency rooms, critical care, laboratories

**1.2. Manufacturer:**

Tarkett North America      Phone:      (800) 899-8916  
30000 Aurora Rd.                                      (440) 543-8916  
Solon, Ohio 44139  
Web: www.tarkettna.com

**1.3. Proprietary Product Description:**

- 1.3.1. **Construction:** Tarkett iD Latitude is constructed on a unique composite structure built with homogeneous polymeric calendared layers with a 20 mil PVC wear layer. Techtonic polyurethane coating technology is super tough; resisting scratching, abrasions, scuffing and staining to ensure your floor look nicer, longer.

**1.3.2. Characteristics:**

- **Finish:** Techtonic
- **Edge treatment:** Square Edge
- **Wearlayer Thickness:** .020" (0.5 mm)
- **Overall thickness:** 0.120" (3.0 mm)
- **Designs:** 22 Wood, 14 Abstract, 8 Stone/Concrete

**1.3.3. Tile/Plank size and Packaging:****Abstract**

- 6" x 36" (15.2 cm x 91.4 cm), 24 planks/ctn, 36 sq. ft./ctn (3.34 m<sup>2</sup>/ctn), 36 lbs/ctn (16.33 kg/ctn), 66 ctn/pallet

**Wood**

- 6" x 48" (15.2 cm x 121.9 cm), 18 planks /ctn, 36 sq. ft./ctn (3.4 m<sup>2</sup>/ctn), 36 lbs/ctn (16.33 kg/ctn), 72 ctn/pallet

**Abstract, Stone & Concrete**

- 18" x 18" (45.7 cm x 45.7 cm), 20 tiles /ctn, 45 sq. ft./ctn (4.18 m<sup>2</sup>/ctn), 45 lb/ctn (20.41 kg/ctn), 60 ctn/pallet

**2. PRODUCT PERFORMANCE AND TECHNICAL DATA**

- 2.1. **Tile material** – Meets ASTM F1700, Class III, Type B performance standards for solid vinyl floor tile
- 2.2. **Wear layer thickness:** 20 mil
- 2.3. **Residual Indentation** (ASTM F1914): Passes

- 2.4. **Static coefficient of friction** (ASTM D2047):  $\geq 0.5$  SCOF, ADA compliant
- 2.5. **Static Load Limit** (ASTM F970): 250 psi,  $\leq 0.005$  inches
- 2.6. **Dimensional Stability** (ASTM F2199): Passes
- 2.7. **Resistance to Heat** (ASTM F1514):  $\Delta\Sigma \leq 8.0$
- 2.8. **Resistance to Light:** (ASTM F1515):  $\Delta\Sigma \leq 8.0$
- 2.9. **Chemical Resistance** (ASTM F925): Passes
- 2.10. **Flammability** (ASTM E648, CRF):  $\geq 0.45$  W/cm<sup>2</sup> (Class 1)

**3. INSTALLATION**

See iD Latitude Luxury Vinyl Tile and Plank installation instructions for complete details.

**3.1. Adhesives:**

- **Tarkett RollSmart Adhesive:**  
Coverage: 350 - 400 sq. ft. per gallon  
(3/8" Nap Paint Roller used with a paint tray)
- **Tarkett 959 Adhesive:**  
Coverage:  
Porous Substrate: 150-175 sq. ft. per gallon  
Non-porous Substrate: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Polyurethane Adhesive:**  
Approximate Coverage:  
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon

**4. AVAILABILITY AND COST**

Available through Tarkett dealers nationwide.

**5. WARRANTY**

Limited 20 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

**6. MAINTENANCE**

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to iD Latitude Maintenance Instructions for complete maintenance details.

**7. TECHNICAL SERVICES**

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at 1-800-899-8916.

**Tarkett North America**

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkettna.com](http://www.tarkettna.com)