

Features

- **Unmatched Installation Ease.** Innovative parallelogram floorboard includes five chevron planks, making it a smooth installation process featuring the innovative and strongest Välinge 5G® locking system.
- **Authentic Grain Embossing.** Experience the natural beauty with enhanced grain embossing that ensures visual continuity across planks.
- **Superior Durability.** Equipped with a commercial-grade wear layer, our flooring is built to withstand the demands of daily life, maintaining its pristine appearance for years to come.
- **Color Matching Planks To Suit Your Flooring Needs.** Our Color Matching Planks are crafted with attention to detail to achieve an exact match to your desired flooring.
- **100% Waterproof .** Enjoy the stability of a high-density, waterproof core that is both warmer and more flexible than standard options.
- **Eco Friendly & Child Safe.** Free from phthalates and FloorScore certified, our flooring is safe for both children and pets.
- **Built-In Cork Underlayment.** Designed to provide a luxurious feel underfoot and promote a healthier indoor environment, our cork underlayment offers antimicrobial protection and contributes to a comfortable and supportive foundation.



Product Information

| | |
|-----------------------------|---|
| Product Line | SureWood Chevron Luxury Vinyl Flooring |
| Construction | WPC (wood polymer composite) vinyl |
| Dimension | 8mm (T) x 305mm (W) x 718.4mm (L) 5/16" (20mil wear layer) x 12" x 28-1/4" |
| Underlayment | 1.5mm antimicrobial cork underlayment |
| Wear Layer Thickness | 0.5mm (20 mil) |
| Finish | 2-pass UV cured Urethane Finish |
| Installation | Floating installation by clicking the end joints together. Please refer to Installation Instruction |
| Warranty | Lifetime Residential and 12-Year Commercial Limited Warranty |

Testing

| Classification | Method | Result |
|---|---------------|--|
| Class | ASTM F1700 | Class III, Type B - Embossed |
| Slip Resistance | ASTM C1028-07 | Dry: 0.80; Wet: 0.71 |
| Static Load | ASTM F970 | Applied Load: 1000 psi, Residual Indentation: 0.04mm |
| ΔIIC | ASTM E2179-03 | 23 |
| IIC | ASTM E492-09 | 72 |
| STC | ASTM E90-09 | 71 |
| Dimensional Stability | ASTM F2199 | Pass: ≤0.02 in. per linear foot |
| Resistant to Chemicals | ASTM F925 | Pass: Not affected |
| Abrasion | ASTM D4060 | Test Revolutions: 1000, 0.004% mass loss |
| Antibacterial Activity | ASTM G21-15 | Pass: No growth observed on specimens |
| Reaction to Fire | EN13501-1 | Class B fl-s1 |
| Critical Radiant Flux | ASTM E648 | Pass, >0.45 watts/cm² |
| Concentration of Dibutyl Phthalate | ISO 16000 | <1 µg/m³ after 28 days |
| Concentration of Diethylhexyl Phthalate | ISO 16000 | <1 µg/m³ after 28 days |
| Flexibility | EN435 | No Damage |

Specifications are subject to nominal manufacturing variance.
Material supply and/or manufacturing processes may necessitate changes without notice.

| Packaging Information | | | | | |
|-----------------------|----------------|---------------|-------------------|-----------------------|----------------------------|
| | Length (mm) | Width (mm) | Thickness (mm) | Sq. ft. per Carton | Weight (lb. per carton) |
| Plank Size | 718.4 | 305 | 8 | | |
| Plank Carton | 1060 | 330 | 85 | 23.6 | 40 |

| Pallet Information | | | | | | | |
|---------------------|----------------|---------------|----------------|-----------------------------|---------------------------|--------------------|-----------------|
| | Length (mm) | Width (mm) | Height (mm) | Volume (m ³) | # of carton per Pallet | Sq. ft. /pallet | Weight (lb.) |
| Plank Pallet | 1060 | 1320 | 1035 | 1.45 | 44 | 1038.4 | 1790 |